

## Panora



### FEATURES:

- 4K surge protection
- -10° to +10° tilting
- Operating temperature range -40° to 40°C
- Minimum lumen maintenance: 50 000h (L80B10)

Ordering example: Product Name/Size/CRI/Kelvin/Wattage/Optics (e.g. Panora/L/70/40/120/ORW)


Input Power	LED-Modules	Colour Consistency	Installation Type	Material	Optics
220-240 V	CRI 70+	3 or 5-Step MacAdam	Pole Mounted	Aluminium Alloy	Various

### COB luminous flux:

CODE	CRI	K	W (system)	Lm
Panora/L/70/40/78	70+	4000K	78W	11000Lm
Panora/L/70/40/157	70+	4000K	157W	22000Lm
Panora/L/70/40/223	70+	4000K	223W	30000Lm
Panora/L/70/40/271	70+	4000K	271W	37000Lm
Panora/L/70/40/332	70+	4000K	332W	45000Lm

### KELVIN OPTIONS:

- 2700K
- 3000K
- 4000K
- 5700K



### SIZE OPTIONS:



### OPTIC OPTIONS:

<p><b>ORW</b></p>	<p><b>ORSH</b></p>	<p><b>OP</b></p>	<p><b>A45 - optics for roundabouts</b></p>	<p><b>ORS</b></p>	<p><b>ORWY</b></p>	<p><b>OPB</b></p>
-------------------	--------------------	------------------	--	-------------------	--------------------	-------------------

For complete technical brochure, please contact your Province Lighting representative